



Submersible vortex drainage pump fitted with cast iron semi vortex impeller. Can pump particles up to 15mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Handy carry handle
- Hose tail adaptor included
- 240V single phase motor with built-in thermal overload protection
- 10m of power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering of cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 15mm dia.) and stringy material in suspension.
- Max Flow 150 L/min
- Max head 7.5 m

Liquid:

Liquid water temperature range: 2 – 35 °C

Materials:

Pump body: Cast Iron
 Impeller: Cast iron/Nylon
 Shaft: Stainless Steel
 Shaft seal: Dual mechanical seal - carbon/ceramic and oils seal

Installation:

Maximum ambient temperature: 40 °C
 Pipe connections discharge: 1 1/4"

Electrical data:

Rated voltage: 240V
 Mains frequency: 50 Hz
 Rated output: 250W
 Current: 1.8 amps
 Capacitor: 9 uF
 Motor duty: Continuous
 Motor type: Asynchronous
 Motor protection: Built-in thermal overload
 Ingress protection: IP 68
 Insulation class: B
 Power cable length: 10 m H07RNF
 Net weight: 10 kg

2 Year Bianco Pumpz Warranty

