



**IMPORTANT NOTES TO READ...!!!**

- **2 PERSONS + DRIVER REQUIRED TO HANDLE TANK.**
- DRAWING SHOWS ALL AVAILABLE OUTLET & OVERFLOW POSITIONS. STANDARD INSTALLATIONS HAVE ONLY 1 OUTLET & 1 OVERFLOW
- PLEASE REFER TO 'EASY 6 STEP TANK INSTALLATION GUIDE' FOR INSTRUCTION TO INSTALL ACCESSORIES.
- ALL DIMENSIONS ARE IN METRES AND ROUNDED TO THE NEAREST CENTIMETRE.
- CAPACITIES AND MEASUREMENTS ARE TESTED IN ACCORDANCE TO AS4766, BUT MAY VARY DUE TO THE ROTO-MOULDING PROCESS.
- BUSHMANS RECOMMENDS TOP AND SIDES CLEARANCE OF 100MM MINIMUM WHEN ESTIMATING SPACE REQUIRED FOR THE TANK.

**BUSHMANS GROUP PTY LTD**

HEAD OFFICE : Level 13, 300 George St, Sydney, NSW 2000  
 Ph 1800 00 88 88 WWW.BUSHMANTANKS.COM .AU

Copyright 2011 Bushmans Group Pty Ltd. This drawing may not be reproduced or transmitted in any form or by any means in part or whole without written permission of Bushmans Group Pty Ltd.

Drawn S.NAGY  
 Date 31.03.15  
 Scale 1:40

Project Title TXD2300 V001  
 Material POLYETHYLENE  
 Finish

Drawing Title TXD2300 ROUND 10,000 LITRE TANK TANK SALES DRAWING