



## BIANCO VULCAN 3.0 HP PORTABLE PETROL ENGINE PUMP

The pump is a light weight self priming engine driven pump supplied ready to operate with hose fittings and suction strainer.

**The pump is characterised by:**

- Single Cylinder, 4 Stroke, Forced Air Cooled OHV Engine
- Heads to 25 metres
- Flows to 300 l/min
- Suction to 8m
- 1-1/2" BSP Male Discharge Port
- 1-1/2" BSP Male Suction Port
- Carry Frame
- Rubber Mounting Feet

**Features:**

- Custom Built Frame
- Spark Arrester
- Full Serviceability Without Removing Pump from Frame

**Applications:**

- Dust Suppression
- Water Transfer
- Tank Filling
- De-watering

| Liquid:  | Engine Data:                                   |
|--|--|
| Liquid Type: Clean Water<br>Clean water temperature range: 2 - 35° C | Type: Single Cylinder, Aircooled, 4 Stroke OHV |
| <b>Materials:</b>  | Model: G87                                     |
| Pump Body: Aluminium   | HP gross: 3.0                                  |
| Impeller: Aluminium  | Displacement: 87 cc                            |
| Mechanical Seal: Carbon/Ceramic/Nitrile                              | Air Cleaner: Dual Element, Paper and Foam      |
| O rings: Nitrile   | Ignition: CDI                                  |
| <b>Installation:</b>   | Starting: Recoil                               |
| Maximum ambient temperature: 40°C                                    | Fuel Capacity: 1.8 Litre                       |
| Self Priming Time at 5m: <120 seconds                                | Oil Capacity: 0.35 Litre                       |
| <b>Weight:</b>   |  |
| 14.5kg   |  |

