



POSITIVE "CLICK" SMOOTH OPEN/CLOSE ACTION

Smooth action open and close helps reduce surge which can cause damage to your system. Positive 'click' gives the assurance the valve is either on or off.



HIGH QUALITY MATERIALS

- Body & End Caps - Glass Fibre Reinforced Nylon
- Handle - Glass Fibre Reinforced Nylon
- Ball - Polypropylene
- Ball Seats & Stem - Acetal (POM)
- O-Rings - EPDM



REMOVABLE HANDLES
Removable Handles for Security and Varying Applications



HAND TESTED
All Hansen Full Flow Ball Valves are rigorously hand tested.

Male/Female Ball Valves available in sizes 25 to 50mm

DIFFERENT HANDLES FOR VARYING APPLICATIONS

Available as separate accessories.

- BLUE Handles for general applications
- LILAC Handles for grey water applications
- GREEN Handles for increased visibility and to differentiate

MALE/FEMALE OR FEMALE THREAD OPTIONS

Available in various thread options to suit a range of applications



MAXIMUM WORKING PRESSURE
16 Bar (235 psi)
@ 20°C



FULL FLOW BORE

Unrestricted Full Flow Ball Valve gets the job done faster. Less system strain, lower maintenance costs. High Pressure 16 Bar Rated.

Female Ball Valves available in sizes 15 to 50mm



Salt Water Friendly



Frost Friendly

FROST FRIENDLY

Hansen Ball Valves are Frost Friendly and have been tested in frost conditions. Results may vary in freezing conditions.



Retail Packaging



AS/NZS 4020:2018 CORROSION PROOF & POTABLE WATER APPROVED

Manufactured from non-corrosive, UV Stabilised Materials. Potable Water & Marine Approved and Salt Water Friendly.



HANSEN™

Full Flow Ball Valves

Full Flow Reliable High Performance Ball Valve

www.hansenproducts.com