

Submersible Pressure Pump BLUEDIVER

- ▶ Compact
- ▶ Auto on/off Float Switch
- ▶ Overheating Protection
- ▶ Stainless Steel Filter
- ▶ Designed in Italy



3
YEAR
WARRANTY



**Adjustable
Float**



**Stainless Steel
Filter**



Float



Model	BLUEDIVER C30	BLUEDIVER C40
Electrical data	P1 Power consumption [W]	900
	P2 Pump consumption [W]	650
	Voltage [V]	1 ~ 220-240 AC
	Frequency [Hz]	50
	Current [A]	3.8
	Capacitor μ F	12.5
	Capacitor Vc	450
	Rated speed [1/min]	2.850
Hydraulic data	Flow rate max. [l/min]	95
	Max. Pressure [Bar]	3.6
	Max. Head [m]	36
	Max. working pressure [bar]	6
	Max depth of immersion [m]	12
Range of use/materials	Length of Power Cable [m]	15
	Cable	H07 RNF
	Pump International protection	IPX8
	Insulation Class	F
	Liquid range Temperature [°C]	0 °C / +35 °C
	Dimension of particles [mm]	clean water
	Max. Ambient Temperature [°C]	+40 °C
Dimensions / weight	L x W x H [mm]	150 x 150 x 400
	DNM GAS	1" F
	Box Dimensions l x w x h [cm]	23 x 19 x 46
	Net/Gross Weight [kg]	8.7/10
	Quantity for pallet [no.]	40

