STORMWATER PIT + PUMP SYSTEM

Stormwater, pumped away.

ASC 175 litre pre-plumbed stormwater pit with ASC D18VAMAG pump

PRE-PLUMBED | PLUG & PLAY | AUTOMATIC OPERATION | FREE DELIVERY

PRE-ASSEMBLED & READY TO GO



Photo shows the optional ball valve.



SKU 175LT-PIT-D18VAMAG

KEY SPECIFICATIONS

Pit capacity	175 litres
External dimensions	716 (L) × 716 (W) × 658 (D) mm
Grate	Galvanised steel, AS3996 Class A
Pump	ASC D18VAMAG semi-vortex drainage pump, cast iron body & impeller
Max flow	135 L/min
Max head	6.7 m vertical lift
Solids handling	Up to 15 mm
Float switch	Automatic vertical float — starts at 300 mm, stops at 120 mm
Outlet	50 mm threaded BSP brass
Valve	40 mm flap non-return valve included; ball valve optional
Power lead	10 m H07RNF cable, Australian 3-pin plug
Pit empty weight	38 kg
Options	300 mm extension riser Ball valve (shown in photo)
Warranty	2 years

WHERE TO USE IT

- **Garages & driveways** prone to flooding
- **Patio edges** & paved courtyards
- **Around pools** surrounds & decks
- **Cellars & basements** sump dewatering
- **Clay-soil backyards** that won't drain
- **Carparks** in non-vehicle trafficable areas
- **Light industrial** factory waste & sites
- **Underdecks** beneath decks & verandahs

2 Park Drive, Dandenong South VIC 3175

CALL (03) 8795 7715

EMAIL sales@asctanks.com.au

VISIT asctanks.com.au