



STORMWATER PIT + PUMP SYSTEM

Stormwater, pumped away.

ASC 75 litre pre-plumbed stormwater pit with ASC D18VAMAG pump

PRE-PLUMBED

PLUG & PLAY

AUTOMATIC OPERATION

FREE DELIVERY

PRE-ASSEMBLED & READY TO GO



SKU 75LT-PIT-D18VAMAG

KEY SPECIFICATIONS

Pit capacity	75 litres
External dimensions	562 (L) × 562 (W) × 506 (D) mm
Grate	Galvanised steel, AS3996 Class A
Pump	ASC D18VAMAG semi-vortex drainage pump, cast iron body & impeller
Max flow	135 L/min
Max head	6.7 m vertical lift
Solids handling	Up to 15 mm
Float switch	Automatic vertical float — starts at 300 mm, stops at 120 mm
Outlet	40 mm (1½") BSP threaded brass
Valve	40 mm flap non-return valve included; ball valve optional
Power lead	10 m H07RNF cable, Australian 3-pin plug
Pit empty weight	16.65 kg
Options	300 mm extension riser (560 × 560 mm)
Warranty	2 years

WHERE TO USE IT



Garages & driveways
prone to flooding



Patio edges
& paved courtyards



Around pools
surrounds & decks



Cellars & basements
sump dewatering



Clay-soil backyards
that won't drain



Carparks
in non-vehicle
trafficable areas



Light industrial
factory waste & sites



Underdecks
beneath decks &
verandahs



2 Park Drive, Dandenong South VIC 3175

CALL

(03) 8795 7715

EMAIL

sales@asc tanks.com.au

VISIT

asc tanks.com.au