



Stormwater, pumped away.

ASC 75 litre pre-plumbed stormwater pit with ASC D25VAMAG pump

PRE-PLUMBED

PLUG & PLAY

AUTOMATIC OPERATION

FREE DELIVERY

PRE-ASSEMBLED & READY TO GO



SKU 75LT-PIT-D25VAMAG

KEY SPECIFICATIONS

Pit capacity	75 litres
External dimensions	562 (L) × 562 (W) × 506 (D) mm
Grate	Galvanised steel, AS3996 Class A
Pump	ASC D25VAMAG vortex drainage pump, cast iron body & impeller
Max flow	165 L/min
Max head	9.0 m vertical lift
Solids handling	Up to 15 mm
Float switch	Automatic vertical float — starts at 310 mm, stops at 200 mm
Outlet	65 mm external / 50 mm internal threaded BSP brass
Valves	50 mm flap valve and 40 mm ball isolation valve included
Power lead	10 m H07RNF cable, Australian 3-pin plug
Options	300 mm extension riser (560 × 560 mm)
Warranty	2 years

WHERE TO USE IT



Garages & driveways
prone to flooding



Patio edges & paved courtyards



Around pools
surrounds & decks



Cellars & basements
sump dewatering



Clay-soil backyards
that won't drain



Carparks
in non-vehicle
trafficable areas



Light industrial
factory waste & sites



Underdecks
beneath decks &
verandahs

